



Access control

The Nylofor swing gates are available in single and double version with Nylofor infill as a perfect combination with nylofor panel fences.

Nylofor[®] swing gates

Benefits

Rigid construction

All elements of the Nylofor swing gates are of an extremely rigid construction: frame, Nylofor panels and postsystem.

Optimal setting

The locking system allows optimal setting and is easy to install.

Fully adjustable hinges

The hinges are adjustable and allow each leaf to swing through 180°.

High quality coating

The Nylofor swing gates receive the best coating that exists today.

Rapid installation

The Nylofor swing gates are designed for quick installation: the accessories are limited to a minimum.

Applications

The industrial swing gates Nylofor are recommended wherever industrial safety and security are crucial: factories and workshops, administrative centres, public buildings, play- and sport grounds, schools, parks, airports and military sites.



Frame

Frame out of square tube 60 x 60 or 80 x 60 mm, with welded Nylofor infill.

Posts



Square posts out of welded tube with cap, and fixation strips for the fixation of the fencing panels to the gate posts by means of special clamps.

Accessories

Hinges: adjustable hinges, allowing the wings to be opened 180°.

Lock system: composed of lock slot, counter lock, integrated lock with cylinder and handle.

Ground bolt: for single and double swing gates. Manufactured from stainless steel and attached to each wing, to be anchored into the central floor plate (double gates).

Coating

Galvanised and polyester coated.


Colours

Green RAL 6005 - White RAL 9010

Other colours: on request

CE Marked


Nylofor gates are CE marked according to the European directive: Construction products directive (89/106/CE) and type tested according to standard EN 13241-1 for Industrial, commercial and garage doors and gates.




Post with fixation strip.



Adjustable hinge.



Lock system.



Ground bolt.

ASSORTMENT SWING GATES NYLOFOR 3D

Width (mm)	Height (mm)	Free passage (mm)	Space needed fixing strip included (mm)
Single swing gates			
1000	1030/1230/1530/1730/2030/2430	920	1110
1500	1030/1230/1530/1730/2030/2430	1470	1660/1700*
2000	1030/1230/1530/1730/2030/2430	1970	2160/2200**
2500	1030/1230/1530/1730/2030/2430	2470	2740
3000	1030/1230/1530/1730/2030/2430	3000	3270/3310*
Double swing gates			
3000	1030/1230/1530/1730/2030/2430	2900	3090/3130*
4000	1030/1230/1530/1730/2030/2430	3900	4090/4130**
5000	1030/1230/1530/1730/2030/2430	4900	5170
6000	1030/1230/1530/1730/2030/2430	5960	6230/6270*
8000	1030/1230/1530/1730/2030/2430	7980	8290/8330*
10000	1030/1230/1530/1730/2030/2430	9980	10330

Other dimensions on request. * for height 2430 mm **for heights 1730 - 2030 - 2430 mm

ASSORTMENT SWING GATES NYLOFOR F, 2D AND 2D SUPER

Width (mm)	Height (mm)	Free passage (mm)	Space needed fixing strip included (mm)
Single gates			
1000	1030/1230/1430/1630/1830/2030	920	1110
Double gates			
3000	1030/1230/1430/1630/1830/2030	2900	3090
4000	1030/1230/1430/1630/1830/2030	3900	4090/4130*
5000	1030/1230/1430/1630/1830/2030	4900	5170
6000	1030/1230/1430/1630/1830/2030	5960	6230
8000	1630/1830/2030	on request	on request
10000	1630/1830/2030	on request	on request

Other dimensions on request - * for heights: 1830 - 2030 mm

